

EUCO - ELASTIC - JOINT

Description: **EUCO - ELASTIC-JOINT** is a one component , cold applied , ready to use, elastic joint filler based on bitumen rubber .

Fields of application :

EUCO - ELASTIC - JOINT is a highly elastic joint filler for sealing the vertical and horizontal joints in buildings. The product can withstand the normal movement of the expansion joints in the structure It also offers a very good waterproofing and chemical resistance characteristics as well as abrasion resistance . **EUCO- ELASTIC - JOINT** adheres very well to most of the commonly used surfaces in construction such as concrete , brick gypsum , stone etc. .

Technical data :

Appearance	paste .
Colour	Black
Specific Gravity	1,35 : 1.45 . (gm/C3)Approx
Pot life	4 - 8 Hrs
Shelf life	2 Years in closed drums .
Complies with ASTM D - 1850	

Application :

- 1-**The inside faces of the joint must be clean, sound free of dust , loose particles , grease and other impurities which can act against good adhesion If necessary use iron brushes .
- 2-**Determine the clear depth of the joint which will be filled with **EUCO-ELASTIC-JOINT** by using a closed cell polyethylene foam or foam rubber or polystyrene sheets .
- 3-**For the high porous surfaces apply Euco Bitumen Primer to seal the surface before applying the filler .
- 4-**Apply **EUCO - ELASTIC - JOINT** using knife or spatula to fill the joints and to insure complete sealing .

Packing

Drums of : 20 - 125 liters .