

EUCOPREN
Thixotropic Sealing Material

- Product** Solvent free , thixotropic sealing material with a bitumen-rubber
- Description** **EUCOPREN** is an air-drying one component sealing material .When properly dries out it becomes waterproof and permanently elastic .
- Fields of Application** Sealing material for walls , kiln bed-plate etc...
EUCOPREN is an excellent cold insulation material in underground constructions with a permanent elasticity to cover cracks .

Product Characteristics

EUCOPREN is resistant against diluted chemicals but not against mineral oils , diesel etc. .

Technical Data	Appearance	pasty , thixotropic
	Specific gravity	1,08
	Min. . drying temperature	+ 2oC to + 40oC
	Bone dry	approx. 2 h
	Thorough hardened	approx. 2 - 3 days
	Consumption per m2	approx. 3 kg
	Temperature resistance	-25o up to + 100oC
	Storage life in months at 20oC	12 month protected against frost.

Surface Application Cement bound surfaces should be dry ,firm , of good traction and free of dust and dirt particles , and additionally free from oil , grease and other impurities which can act against good adhesion .If necessary , sand blast , brush or grind .

Application **EUCOPREN** is supplied ready for use and is applied with trowel or spatula .The surface must be clean , sound and free from loose particles Surface can be damp but not wet .
Material consumption approx. 3 kg/ m2 .

Colour Black .

Packing Containers of 20 kg & Drums of 200 kg .