

EUCOSMOOTH READY TO USE PLASTERING

Description **EUCOSMOOTH** is a ready to use plastering based on treated gypsum with a slow setting time, keeps the mixing water for a while . Which gives enough time for good finishing and smoothing .

Advantages **1-EUCOSMOOTH** is produced specially for plastering on smooth surfaces like fare face concrete without special preparation or chipping the concrete surface.
2-Very good adhesion to the concrete or masonry without any primers.
3-EUCOSMOOTH gives a very smooth surface which can be considered a finished surface without painting.
4-EUCOSMOOTH forms a light weight layer but very hard and strong.
5-Successfully fills in cracks or honey comb if it exists on the concrete surface.
6-EUCOSMOOTH is economic in consumption.

Technical data	Hardening time	50-60 min.
	Chloride content	nil
	Colour	off White
	Mixing with water	1 water : 3 EUCOSMOOTH
	Shelf life	one year

Consumption	Thickness	Consumption
	1 mm	1 kg/m ²
	5 mms	4-5 kg/m ²
	30 mms	25-30 kg/m ²

Application **1-** Surface must be clean free of dirties, dust, oils, or grease.
2-Add water to **EUCOSMOOTH** until mortar is ready with thixotropic consistency.
3- Apply **EUCOSMOOTH** one layer.
Up to 30 mms. thickness to the surface.

Package Bags 30 kg.