

Plasto Matt Interior Emulsion Paint

Description **Plasto Matt** is a plastic emulsion matt paint. anti rub, alkali resistant and non yellowing paint.

Field s of

Application: **Plasto Matt** is used for interior uses, on old as well as new plaster and concrete, and also as a primer for wall paper.

Technical Data:

Finish	Flat
Solids by volume	42% (approx)
Solids by weight	61%
Theoretical Spreading rate	5.5 m ² /kg (50 m dry)
Dry film thickness	50 Microns.
Wet film thickness	120 Microns.
Recommended D.F.T	150 Microns.
Specific gravity	1.5 gm/cm ³
Thinner	Tap water.
Drying time	
Surface	0.5 hr (at 25 oC. 60% R.H)
Full cured	7 days (at 25 oC. 60% R.H)
Recoat interval	
Min	1-2 hrs (at 25 oC. 60% R.H)
Max	No limitation
Shelf life	Up to 1 year.
Application method	By Brush and roller
Volume of thinner	0-10%.
Packing	20 Kg.

Mode of Application **Plasto Matt** must be stirred thoroughly before use the method of application depends on type of surface:

1- Porous surfaces like new, old untreated walls, and ceilings , should be primed with diluted **Plasto Matt** then it is reduced to normal brushing or roller consistency to be applied as top coat.

2- Non porous surfaces like old walls and wood which have previously been painted should first be washed with a solution of ammonia and then painted with **Plasto Matt** reduced to the normal consistency.

N.B Brush and roller should be cleaned thoroughly in pure water immediately upon application. As dry **Plasto Matt** is difficult to dissolve.