EUCOGUNITWater proofing and quick setting

Description

EUCOGUNIT is a quick setting and waterproofing compound for sprayed concrete and Gunit, which allows spraying concrete and mortar even on a wet surface or one subject to slight infiltration.

EUCOGUNIT speeds the work and contributes to good water tightness of the sprayed concrete linings if the aggregate materials are chosen carefully.

The admixture facilitates overhead spaying and reduces rebound.

Application

EUCOGUNIT is used with sprayed concrete and mortar in galleries

And tunnels, for retaining walls and embankment linings, sheds, tanks etc..

Instruction for use

EUCOGUNIT is supplied in powder form ready for use. Dosage is between 3% and 7% by weight of cement. The normal effect is fully achieved with 3%

- 4% .Dosages of 5% - 7% result in much quicker setting or hardening .

The required amount of **EUCOGUNIT** is mixed with the dry sand- cement or gravel -sand -cement mixture. Large quantities of dry mix can be prepared if protected against moisture.

When guniting is interrupted, care must be taken that the water dose not flow back in the supply hose causing the mix to set.

Larger infiltration of water must be sealed off with **EUCORAPID** or drained off.

Concrete or mortar sprayed with **EUCUGUNIT** requires a covering layer without accelerator.

storage

Shelf life in undamaged bags is unlimited when stored in a dry place.

EUCOGUNIT is insensitive to frost.

Important indication

Setting is slowed down due to different circumstances

- 1- Using cold cement, cold sand or, cold water.
- 2- Having very cold ambient weather which results in a very cold surface.
- 3- Old cement.

Packing

EUCOGUNIT, white powder, in bags of 25 kg or drums of 170 kg.