

## **Eucocoat super Emulsion paint**

**Description** **Eucocoat super** is a plastic math, anti rub, alkali resistant and non yellowing paint.

### **Field s of**

**Application:** **Eucocoat super** is used for interior uses, on old pre-plastered walls and concrete, and as under coat for wall paper.

### **Technical Data:**

<b>Finish</b>	Flat
<b>Solids by volume</b>	34%
<b>Solids by weight</b>	53%
<b>Spreading</b>	0.50 m <sup>2</sup> /kg (50 m dry)
<b>Dry film thickness</b>	50 Microns.
<b>Wet film thickness</b>	148 Microns.
<b>Recommended D.F.T</b>	150 Microns.
<b>Specific gravity</b>	1.4 gm/cm <sup>3</sup>
<b>Thinner</b>	Tap water.
<b>Drying time</b>	
<b>Surface</b>	5 hr (at 25 oC. 60% R.H)
<b>Full cured</b>	7 days (at 25 oC. 60% R.H)
<b>Recoat interval</b>	
<b>Min</b>	1-2 hrs (at 25 oC. 60% R.H)
<b>Max</b>	No limitation
<b>Shelf life</b>	Up to 1 year.

**Application methods** - By Brush and roller:  
- Volume of thinner :0-10%.

**Mode of Application** **Eucocoat Super** must be stirred thoroughly before use  
method of application depends on type of surface:

1- Porous surfaces like new, old non treated walls, and ceilings , should be primed with diluted **Eucocoat Supper** then it is reduced to normal brushing as top coat .

2- Non porous surfaces like old. walls and wood which have previously been painted with an oil painted should first be washed with a solution of ammonia and then painted with **Eucocoat Supper** reduced to the normal consistency

**Packing** Drums 5 Kg , 20 Kg.