

**EUCOCURE HB**  
**Concrete curing membrane**

<b>Description</b>	<b>EUCOCURE HB</b> is a curing compound based on selected synthetic resins and solvents.	
<b>Main Purpose</b>	To protect fresh concrete surfaces from the undesirable effects associated with too rapid evaporation of surface moisture. This protection is achieved by spraying <b>EUCOCURE HB</b> on to the fresh concrete surface which rapidly forms an impermeable skin over the concrete surface .	
<b>Advantages</b>	<b>EUCOCURE HB</b> provides a labour saving method of protecting all fresh concrete without the use of continuous wetting , wet sand , wet mats , ... etc. when used in accordance with our instructions , the film will disintegrate and flake off from the surface through traffic and weathering .	
<b>Standards</b>	Complies with ASTM C - 309 - 89 2, DIN and SIA Standards ASHTO T 155, ASTM C - 156-89	
<b>Properties</b>	Appearance	liquid
	Colour	Light Brown
	Specific gravity	0,9
	Open flash point	40oC
	Shelf life	up to 2 years
	Complies with ASTM C - 309 . ASHTO T 155 , ASTM C - 156 - 89	
<b>Coverage</b>	6 to 8 m <sup>2</sup> per 1 kg <b>EUCOCURE HB</b> Can be applied by hand-operated or power-driven spray guns.	
<b>Remarks</b>	<b>EUCOCURE HB</b> contains solvents and is flammable keep away from open fire.	
<b>Packing</b>	In drums containing 200 kg .	